



| Product Advantages | |
|--|--|
| Energy saving up to 80% compared to conventional lighting fixtures | |
| High efficiency LED light system | |
| Long life, high quality LED and high efficiency driver | |
| For corrosion resistance, zincoprism applied to surface of the luminaire before electrostatic powder coating | |
| Inox bolts | |
| High quality silicone gasket provides sealing | |

| Product Specifications | |
|------------------------------|---------------------------------------|
| Housing: | Aluminum profile and die cast housing |
| Optical Cover: | Tempered glass |
| Light Source: | Mid Power LED |
| Ingress Protection Rating: | IP65 |
| Electrical Protection Class: | Class 1 |
| Width (a): | 120 mm |
| Height (b): | 60 mm |
| Depth (c): | 180 mm |
| Working Temperature: | -20 °C ~ +50 °C |

| Electrical Properties | |
|----------------------------|-----------------------|
| Nominal Power: | 15 W |
| Operating Mode: | Compatible LED Driver |
| Input Voltage: | 220 - 240 VAC |
| Input Frequency: | 50 - 60 Hz |
| Power Factor: | > 0.90 |
| Current: | 71 mA |
| Total Harmonic Distortion: | < 15 % |
| Control Type: | On - Off Controller |

| Photometric Properties | |
|-------------------------------|-----------------------------|
| Color Temperature: | 3000 °K - 4000 °K - 6500 °K |
| Luminous Flux: | 1475 lm - 1530 lm - 1590 lm |
| Luminous Flux Tolerance: | < 10 % |
| Efficacy: | 106 lm/W |
| Colour Rendering Index (CRI): | ≥ 80 |