



| Product Advantages | |
|--|--|
| Energy saving up to 80% compared to conventional lighting fixtures | |
| High efficiency LED light system | |
| Long life, high quality LED and high efficiency driver | |
| Inox bolts | |
| High quality silicone gasket provides sealing | |

| Product Specifications | |
|------------------------------|---------------------------------------|
| Housing: | Aluminum profile and die cast housing |
| Optical Cover: | Polycarbonate diffuser |
| Light Source: | Mid Power LED |
| Ingress Protection Rating: | IP65 |
| Electrical Protection Class: | Class 1 |
| Diameter (a): | 150 mm |
| Height (b): | 600 / 900 mm |
| Working Temperature: | -40 °C ~ +50 °C |

| Electrical Properties | |
|----------------------------|-------------------------------------|
| Nominal Power: | 22 W |
| Operating Mode: | Compatible LED Driver |
| Input Voltage: | 220 - 240 VAC |
| Input Frequency: | 50 - 60 Hz |
| Power Factor: | > 0.90 |
| Current: | 105 mA |
| Total Harmonic Distortion: | < 15 % |
| Control Type: | 1-10 V / DALI / On - Off Controller |

| Photometric Properties | |
|-------------------------------|-----------------------------|
| Color Temperature: | 3000 °K - 4000 °K - 6500 °K |
| Luminous Flux: | 2178 lm - 2395 lm - 2420 lm |
| Luminous Flux Tolerance: | < 10 % |
| Efficacy: | 110 lm/W |
| Colour Rendering Index (CRI): | ≥ 80 |